

Tag-it™ HF-I STANDARD TRANSPONDER INLAYS MINIATURE RECTANGLE

FEATURES

- ISO/IEC 15693-2,-3; ISO/IEC 18000-3 Compliant
- 13.56 MHz Operating Frequency
- 256 Bit User Memory in 8x32-bit Blocks
- Application Family Identifier (AFI)
- Fast Simultaneous Identification (Anti-collision)

APPLICATIONS

- Product Authentication
- Library
- Supply Chain Management
- Asset Management
- Ticketing/ Stored Value

DESCRIPTION

Texas Instruments' Tag-it HF-I Standard Transponder Inlays consist of 13.56 MHz high frequency (HF) transponders that are compliant with the ISO/IEC 15693 and ISO/IEC 18000-3 global open standards. These products offer a user accessible memory of 256 bits, organized in 8 blocks and an optimized command set available in five different antenna shapes with frequency offset for integration into paper, PVC or other substrates.

Tag-it HF-I Standard Transponder Inlays are manufactured with TI's patented laser tuning process to provide consistent read performance. And prior to delivery, the transponders undergo complete functional and parametric testing, in order to provide the high quality that customers have come to expect from TI.

The Tag-it HF-I Standard Transponder Inlays are well suited for a variety of applications including *but not limited to*: product authentication, library applications, supply chain management, asset management, and ticketing/stored value applications.

SPECIFICATIONS

PART NUMBER	RI-I03-114A-01
Supported Standard	ISO/IEC 15693-2,-3; ISO/IEC 18000-3
Recommended Operating frequency	13.56 MHz
Passive Resonance Frequency (at +25°C)	13.86 MHz ± 200kHz (includes frequency offset to compensate further integration into paper or PVC lamination)
Typ. required activation field strength to read (at +25°C)	107 dBµA/m #
Typ. required activation field strength to write (at +25°C)	111 dBµA/m #
Factory programmed Read Only Number	64 bits
Memory (user programmable)	256 bits organized in 8 x 32-bit blocks
Typical programming cycles (at +25°C)	100,000
Data retention time (at +55°C)	> 10 years
Simultaneous Identification of Tags	Up to 50 tags per second (reader/antenna dependent)
Antenna size	22.5 mm x 38 mm (~0.89 in x ~1.5 in)
Foil width	48 mm ± 0.5 mm (1.89 in ± 0.02 in)
Foil pitch	48 mm +0.1mm/-0.4mm (~1.89 in)
Base material	Substrate: PET (Polyethyleneterephthalate) Antenna: Aluminum
Operating temperature	-25°C to +70°C
Storage temperature (single inlay)	-40°C to +85°C (warpage may occur at upper temperature range)

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appear at the end of this data sheet.

RI-I03-114A-01

11-09-22-163 – DECEMBER 2005

Storage temperature (on reel)	-40°C to +40°C
Delivery	Single row tape wound on cardboard reel with 500 mm diameter Reel outer width: approx. 60 mm (~2.36 in) Reel inner width: approx. 50 mm (~1.97 in) Hub diameter: 76.2 mm (3 in)
Typical quantity of good units per reel	5,000

Note: For highest possible read-out coverage we recommend to operate readers at a modulation depth of 20% or higher


After integration into paper; * After PVC Lamination

SUPPORTED COMMAND SET

Request	Request Mode					
	Request Code	Inventory	Addressed	Non-Addressed	AFI	Opt. Flag
ISO 15693 Mandatory and Optional Commands						
Inventory	0x01	✓	-	-	✓	0/-
Stay Quiet	0x02	-	✓	-	-	0/-
Read_Single_Block	0x20	-	✓	✓	-	-/1
Write_Single_Block	0x21	-	✓	✓	-	-/1
Lock_Block	0x22	-	✓	✓	-	-/1

1. ✓ : Implemented
2. - : Not applicable

MEMORY ORGANIZATION



IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products		Applications	
Amplifiers	amplifier.ti.com	Audio	www.ti.com/audio
Data Converters	dataconverter.ti.com	Automotive	www.ti.com/automotive
DSP	dsp.ti.com	Broadband	www.ti.com/broadband
Interface	interface.ti.com	Digital Control	www.ti.com/digitalcontrol
Logic	logic.ti.com	Military	www.ti.com/military
Power Mgmt	power.ti.com	Optical Networking	www.ti.com/opticalnetwork
Microcontrollers	microcontroller.ti.com	Security	www.ti.com/security
		Telephony	www.ti.com/telephony
		Video & Imaging	www.ti.com/video
		Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments
Post Office Box 655303 Dallas, Texas 75265

Copyright © 2005, Texas Instruments Incorporated