



LOW FREQUENCY RFID TAGS ENABLE IMPROVED TRACKING OF PLASTIC WASTE BINS AND CONTAINERS

Easily integrated, yet tamper resistant . inserts securely into standard pre-drilled holes in waste bins and containers

Sturdy . resistant to liquids, thermal fluctuation, vibration and shock

Unsurpassed quality . fully automated HID manufacturing and direct-bonding technology ensure dependable performance

HID Plug Tag transponders enable the cost-effective tagging of plastic residential, commercial and industrial waste containers for tracking usage via radio frequency identification (RFID).

Automated tracking accelerates waste management processes, and enables pay-as-you-throw and recycling incentive programs, while eliminating error-prone and expensive manual data collection methods historically used for these systems.

The durable Plug Tag housing protects embedded electronics, delivering reliable performance in harsh waste management and logistics environments. Each tag is completely waterproof, and consistently readable, even when temperatures dip

to -13° F (-20° C) or rise to 185° F (85° C).

Ridges around the shaft ensure that the RFID tag inserts easily, yet is locked securely into place to prevent tag loss or removal in the field. Plug Tag transponders include read-only memory, in 64 bit UID or 128 bit FDX-b options.

For metallic containers, the HID Bin Tag and IN Tag families include tags that deliver consistent, reliable performance when mounted on metal. In addition, these lines include high frequency and UHF chip options, and available read-write memory up to 2048 bits.

HID will help identify and provide the optimal RFID transponder choice for your application.

TECHNOLOGY HIGHLIGHTS:

100% waterproof (IP68)

Height 0.75 in (19 mm), with diameters of:

- 0.35 in (9 mm) - shaft
- 0.59 in (15 mm) - cap

Integrated chip options:

- Unique, 131 kHz, 64 bit read-only memory
- FDX-b, 134.2 kHz, 128 bit read-only

APPLICATION AREAS:

Waste management

- Residential, commercial and industrial waste bin tracking
- Recycling compliance monitoring
- Improved invoicing and service accuracy
- Route optimization systems
- Incentive-based waste and recycling programs

Returnable transport items

- Perishable produce crates
- Stock system bins



HID can create a custom tag solution to fit your application requirements for chip type, dimensions, programming and materials.

SPECIFICATIONS

	Plug Tag	
	Unique	FDX-b
Base Model Number	601920-001	684921-002
ELECTRONIC		
Operating Frequency	131 kHz ± 6	134.2 kHz ± 6
Chip Type	Unique	FDX-b BDE
Memory	64 bit read-only	128 bit read-only
PHYSICAL		
Dimensions	Ø 0.35 x 0.75 in, cap Ø 0.59 in (Ø 9 x 19 mm, cap Ø 15 mm)	
Mounting Method	Insert into pre-drilled hole	
Affixes To	Plastic	
Housing Material	PA6	
Color	Black	
CHEMICAL AND MECHANICAL		
Water	IP68, 68° F (20° C), 3.3 ft (1 m) x 24 h	
Vibration	IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]	
Shock	IEC 68.2.29 [40 g, 18 ms, 6 axis, 2000 times]	
THERMAL		
Storage	-13° to +185° F (-20° to 85° C), 1000 h	
Operating Temperature	-13° to +185° F (-20° to 85° C)	
OTHER		
Standards		EN 14803, ISO 11785
Options	Alternative colors	
Warranty	7 Years	

North America: +1 949 732 2000
 Toll Free: 1 800 237 7769
 Europe, Middle East, Africa: +41 21 908 01 00
 Asia Pacific: +852 3160 9800
 Latin America: +52 55 5081-1650

ASSA ABLOY
 An ASSA ABLOY Group brand

© 2012 HID Global Corporation. All rights reserved. HID, the HID logo and ceFLEX are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. 2012-01-11-hid-rfid-il-plug-tag-ds-en



For more information, visit: www.rfidcanada.com

Email: info@rfidcanada.com

+1 905-513-8919