



# InLine Tag™ Ultra



## ROBUST, ALL-PURPOSE RAIN® UHF TAGS MOUNT TO ANY SURFACE MATERIAL AND DELIVER LONG READ RANGES

- ▣ **Extreme durability** – resistant to outdoor elements as well as blunt and sharp impact
- ▣ **Multiple mounting options** – glue, screw, rivet or weld
- ▣ **Enhanced reliability** – read-write on any material, up to 26 ft (8 m)
- ▣ **Broadband frequency** – for worldwide use

HID Global's InLine Tag™ Ultra transponders are the most advanced general-purpose RAIN® UHF tags available. Choose from options that mount on any material while enabling read ranges of up to a 26 ft (8 m).

waterproof and resist high-pressure/high temperature washing conditions. The special material and construction of InLine Tag Ultra Pro and Curve provides extra resistance to aggressive chemicals like Caustic Soda.

### TECHNOLOGY HIGHLIGHTS:

- ▣ Worldwide operating frequencies from 860 to 960 MHz
- ▣ Fully interoperable; standards compliant
- ▣ Reliable performance on both metal and non-metal surfaces
- ▣ Waterproof under high pressure / high temperature conditions; chemical and impact resistant
- ▣ Mounting options include nails, screws, rivets, welding and glues
- ▣ Large memory of up to 512-bit user memory and 128-bit EPC

InLine Tag devices improve data collection speed and accuracy for logistics applications, while making tracking more cost-effective. These tags make it possible to identify individual, liquid-filled kegs using RFID readers, as truckloads of them pass through designated points of distribution and delivery.

InLine Tag Ultra RFID tags include HID Global's patented 3D antenna, enabling omnidirectional read range performance independent of mounting material. The larger tags also enable maintenance of separate public and private profiles for added data security.

RAIN UHF technology enables anti-collision functionality, fast data-rate communication and password data protection for precise, reliable reading and updating. All InLine Tag transponders are compliant with EPC global-certified UHF Class 1 Gen 2 readers and modules, including broadband capability for international operations.

The InLine Tag Ultra Curve version is arched to hug metallic kegs or gas cylinders, and durably withstands typical washing and disinfection cycles. Slim versions of the tags enable optimal UHF performance for space-restricted applications, and are configured for attachment via screw or weld.

The tough and versatile InLine Tag transponders are available for mounting on metal, plastic or wood using standard M5 screws, rivets, industrial adhesives or welding. The tags are lightweight,

With the smallest footprint, the Mini version is ideal for tagging roll-cages, boxes, furniture or tools. They attach to any material, and deliver excellent size-to-performance ratios.

**APPLICATION AREAS:**

- **Asset tracking and logistics**
  - Postal and road toll management: truck, wagon and train tracking
  - Supply chain management: pallet and goods tracking
  - Furniture, boxes and tools
- **Returnable transport items**
  - Shipping container tracking
  - Metal keg and gas cylinder identification
- **Waste management**
  - Commercial and industrial bin identification



HID Global can create a custom tag solution to fit your application requirements for chip type, dimensions, programming and materials.



**SPECIFICATIONS**

	InLine Tag™ Ultra				
	Mini	Standard	Slim	Pro	Curve
<b>Base Model Number</b>	6F1987-102	6A7980 (blue) 6A7980-102 (grey) 6A7980-120 (grey, 1D-barcode) 6A7981 (weld)	6A7983 6A7984 (slim weld)	6A7980-401 (blue) 6A7980-402 (grey) 6A7981-402 (weld)	6A7982 -102
<b>ELECTRONIC</b>					
<b>Operating Frequency</b>	865-956 MHz (worldwide)				
<b>Chip Type</b>	Monza R6	Monza 4QT			
<b>Memory</b>	96 bit EPC + 48 bit TID	128 bit EPC + 96 bit TID + 512 bit user memory			
<b>Anti-Collision</b>	Yes				
<b>Reading Distance (2W reader ERP, free space)</b>	Up to 9.8 ft (3 m)	Up to 26.2 ft (8 m)	Up to 16.4 ft (5 m)	Up to 22.9 ft (7 m)	Up to 26.2 ft (8 m)
<b>PHYSICAL</b>					
<b>Dimensions</b>	2.4 × 0.7 × 0.3 in (60 × 18 × 8 mm)	3.8 × 1.1 × 0.6 in (97 × 27 × 15 mm) Weld : 4.1 × 1.4 × 0.6 in (105 × 35 × 15 mm)	3.8 × 1.1 × 0.4 in (97 × 27 × 10 mm) Weld : 4.1 × 1.4 × 0.4 in (105 × 35 × 10 mm)	3.8 × 1.1 × 0.6 in (97 × 27 × 15 mm) Weld : 4.1 × 1.4 × 0.6 in (105 × 35 × 15 mm)	3.5 × 1.5 × 0.6 in (88 × 37 × 14.5 mm); 17.7 in (450 mm) curve radius
<b>Mounting Method</b>	Screw, rivet	Screw, weld			Weld
<b>Screw Mounting Hole</b>	Ø 0.2 in (4.5 mm)	Ø 0.2 in (5.2 mm)			
<b>Affixes To</b>	All surfaces, including metal, plastic, wood				Curved metal
<b>Housing Material</b>	High-impact plastic, Weld : stainless steel ring				
<b>Color</b>	Gray	Pantone blue 287C or grey (custom colors available)			Gray
<b>Weight</b>	0.2 oz (6.3 g)	0.5 oz (16 g) Weld : 0.6 oz (18 g)	0.4 oz (12 g) Weld : 0.5 oz (14 g)	0.8 oz (23 g) Weld : 0.9 oz (26 g)	0.7 oz (20 g)
<b>CHEMICAL AND MECHANICAL</b>					
<b>Water</b>	IP68, IP69K, 176° F (80° C), 100 bar, 30 sek. 16 l/min			IP68, 68° F (20° C), 1 m × 24 h	
<b>Withstands Exposure To</b>	Mineral oil, petroleum, salt mist, vegetable oil; up to 80% humidity at 158° F (70° C)			+ Caustic Soda (5%)	
<b>Environmental Test Conditions</b>	68° F (20° C), 100 h				
<b>Vibration</b>	IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]				
<b>Shock</b>	IEC 68.2.29 [40 g, 18 ms, 6 axis, 2000 times]				
<b>Impact</b>	IEC 62262-IK07	IEC 62262-IK09		IEC 62262-IK08	
<b>Axial/Radial Force</b>	1000 N, 10 sec				
<b>THERMAL</b>					
<b>Storage</b>	-40° to +185° F (-40° to +85° C), 1x1000 h -40° to +185° F (-40° to +85° C), 1x1000 h				
<b>Operating Temperature</b>	-40° to +185° F (-40° to +85° C)				
<b>Shock/Fatigue</b>	-40° to +185° F (-40° to +85° C), 100 x 5 min with 20 sec transition				
<b>OTHER</b>					
<b>Standards</b>	UHF EPC Class 1 Gen 2, ISO 18000-6C, ISO 17364, DIN 40050-9				
<b>Options</b>	Custom embossed logo, no logo or custom tag color. Laser engraving of custom logo, barcode or text on grey tag versions. By default, grey tags are supplied without logo or laser engraving.				
<b>Box Size</b>	250 pcs.	240 pcs.	360 pcs.	240 pcs.	240 pcs.
<b>Warranty</b>	2 Years				



For more information, visit: [www.rfidcanada.com](http://www.rfidcanada.com)  
 Email: [info@rfidcanada.com](mailto:info@rfidcanada.com)  
 +1 905-513-8919